Control Cont					
1020	L Number	Hits			Time stamp
105 induci\$7 near30 (stray adj capacitance) near30 (clock lo oscilla\$6)	-	6817			2004/06/02 18:06
0 scilla\$6) transponder and (induct\$7 near30 (stray adj capacitance) and (clock lo oscilla\$8) 121588 455/\$ ccils .340/\$ ccils .375/\$ ccils . USPAT 2004/06/02 18 146863 455/\$ ccils .340/\$ ccils .375/\$ ccils . USPAT 2004/06/02 18 2004/06/03 09 2004	-	1020			2004/06/02 18:07
1 transponder and (induct\$7 near30 (stray adj capacitance) and (clock to oscilla\$6)) 455/\$.ccls. 340/\$.ccls. 375/\$.ccls. USPAT 2004/06/02 18 2004/06/03 10 2004/06	-	105	induct\$7 near30 (stray adj capacitance) near30 (clock lo	USPAT	2004/06/02 18:17
Cclock to oscilla\$6] 121588 455/\$ ccls. 340/\$ ccls. 375/\$ ccls. 340/\$ cc					
121588 455/\$ ccls. 340/\$ ccls. 375/\$ ccls. USPAT 2004/06/02 18 255/\$ ccls. 340/\$ ccls. 375/\$ ccls. USPAT 2004/06/02 18 2004/06/03 10 2004/06/03 09 2004/06	-	4		USPAT	2004/06/02 18:54
146863 455/\$.ccis. 340/\$.ccis. 375/\$.ccis. USPAT 2004/06/02 18 (induct\$7 near30 (stray adj capacitance) near30 (clock lo oscilla\$6]) and (455/\$.ccis. 340/\$.ccis. 375/\$.ccis.) USPAT 2004/06/02 18 2004/06/03 10 2004/06/03					
18	-				2004/06/02 18:18
Oscilla\$6)) and (455/\$.ccls. 340/\$.ccls. 375/\$.ccls.) 20	-				
1	-	18		USPAT	2004/06/02 18:18
Oscilla\$6) transponder and (induct\$7 near30 (capacitance)) transponder and (induct\$7 near30 stray near30 (capacitance)) USPAT 2004/06/03 10 155 transponder and (induct\$7 near30 stray near30 (capacitance)) USPAT 2004/06/03 10 2004/06/03 09 2004/06/0					
USPAT	-	20		USPAT	2004/06/02 18:42
10				LIODAT	0004/00/00 40 50
155 transponder and ((electromagnetic electro-magnetic) near30 (distance)) 9 transponder and ((electromagnetic electro-magnetic) near30 (decreas\$5 decreas\$4 drop\$5 reduc\$5 fail\$5) near30 USPAT 2004/06/03 09 (decreas\$5 decreas\$4 drop\$5 reduc\$5 fail\$5) near30 DERWENT; IBM_TDB EPO; JPO; DERWENT	-				
Continue	-				
1	-	155		USPAT	2004/06/03 09:11
(decreas\$5 decreas\$4 drop\$5 reduc\$5 fail\$5) near30 (distance) 1 transponder and ((electromagnetic electro-magnetic) near30 (distance)) 21 transponder and ((electromagnetic electro-magnetic) near30 (distance)) 22 transponder and ((electromagnetic electro-magnetic) near30 (decreas\$5 decreas\$4 drop\$5 reduc\$5 fail\$5) near30 (separat\$5)) 22 transponder and ((electromagnetic electro-magnetic) near30 (decreas\$5 decreas\$4 drop\$5 reduc\$5 fail\$5) near30 (separat\$5)) 2004/06/03 09: 09: 09: 09: 09: 09: 09: 09: 09: 09:		•		LICDAT	2004/06/02 00:22
Continue	-	9		USPAI	2004/06/03 09.22
1 transponder and ((electromagnetic electro-magnetic) near30 (decreas\$5 decreas\$4 drop\$5 reduc\$5 fail\$5) near30 (distance))					
(decreas\$5 decreas\$4 drop\$5 reduc\$5 fail\$5) near30 (distance)) transponder and ((electromagnetic electro-magnetic) near30 (decreas\$5 decreas\$4 drop\$5 reduc\$5 fail\$5) near30 (separat\$5)) 15 transponder and ((electromagnetic electro-magnetic) near30 (decreas\$5 decreas\$4 drop\$5 reduc\$5 fail\$5) near30 (between)) 15 transponder and ((electromagnetic electro-magnetic) near30 (decreas\$5 decreas\$4 drop\$5 reduc\$5 fail\$5) near30 (gap)) 15 transponder and ((electromagnetic electro-magnetic) near30 (decreas\$5 decreas\$4 drop\$5 reduc\$5 fail\$5) near30 (gap)) 16 transponder and ((electromagnetic electro-magnetic) near30 (decreas\$5 decreas\$4 drop\$5 reduc\$5 fail\$5) near30 (gap)) 17 transponder and ((electromagnetic electro-magnetic) near30 (decreas\$5 decreas\$4 drop\$5 reduc\$5 fail\$5) near30 (gap)) 18 transponder and (induct\$7 near30 stray near30 (capacitance)) 19 (electromagnetic electro-magnetic) and (induct\$7 near30 stray near30 stray near30 (capacitance)) 29 (electromagnetic electro-magnetic) and (induct\$7 near30 stray near30 (capacitance)) 29 (electromagnetic electro-magnetic) and (induct\$7 near30 stray near30 (capacitance)) 2004/06/03 10 2004/06/03 10 2004/06/03 10 2004/06/03 10 2004/06/03 10 2004/06/03 10 2004/06/03 10 2004/06/03 10 2004/06/03 10 2004/06/03 10 2004/06/03 10 2004/06/03 10 2004/06/03 10 2004/06/03 10		4		EDO: IDO:	2004/06/02 00:16
Comparison Com	-	•			2004/00/03 09.10
transponder and ((electromagnetic electro-magnetic) near30 (distance)) transponder and ((electromagnetic electro-magnetic) near30 (decreas\$5 decreas\$4 drop\$5 reduc\$5 fail\$5) near30 (separat\$5)) transponder and ((electromagnetic electro-magnetic) near30 (decreas\$5 decreas\$4 drop\$5 reduc\$5 fail\$5) near30 (between)) transponder and ((electromagnetic electro-magnetic) near30 (decreas\$5 decreas\$4 drop\$5 reduc\$5 fail\$5) near30 (gap)) transponder and ((electromagnetic electro-magnetic) near30 (decreas\$5 decreas\$4 drop\$5 reduc\$5 fail\$5) near30 (gap)) transponder and ((electromagnetic electro-magnetic) near30 (decreas\$5 decreas\$4 drop\$5 reduc\$5 fail\$5) near30 (gap)) transponder and (induct\$7 near30 stray near30 (capacitance)) 1 (electromagnetic electro-magnetic) and (induct\$7 near30 stray near30 (capacitance)) 29 (electromagnetic electro-magnetic) and (induct\$7 near30 stray near30 (capacitance)) 29 (electromagnetic electro-magnetic) and (induct\$7 near30 stray near30 (capacitance)) 29 (electromagnetic electro-magnetic) and (induct\$7 near30 stray near30 (capacitance)) 29 (electromagnetic) and (induct\$7 near30 stray near30 (capacitance))			1 1		
(distance) DERWENT; IBM_TDB USPAT 2004/06/03 09:	_	21			2004/06/03 09:16
2		21			200-1700700 00.10
1			(distance))		
(decreas\$5 decreas\$4 drop\$5 reduc\$5 fail\$5) near30 (separat\$5)) 15 transponder and ((electromagnetic electro-magnetic) near30 (between)) 16 decreas\$5 decreas\$4 drop\$5 reduc\$5 fail\$5) near30 (between)) 17 decreas\$5 decreas\$4 drop\$5 reduc\$5 fail\$5) near30 (decreas\$5 decreas\$4 drop\$5 reduc\$5 fail\$5) near30 (capacitance)) 2004/06/03 10 2004/06/03 10 2004/06/03 10 2004/06/03 10 2004/06/03 10 2004/06/03 10 2004/06/03 10 2004/06/03 10 2004/06/03 10 2004/06/03 10 2004/06/03 10 2004/06/03 10 2004/06/03 10 2004/06/03 10 2004/06/03 10	_	2	transponder and ((electromagnetic electro-magnetic) near30		2004/06/03 09:18
15		_			
transponder and ((electromagnetic electro-magnetic) near30 (decreas\$5 decreas\$4 drop\$5 reduc\$5 fail\$5) near30 (between)) transponder and ((electromagnetic electro-magnetic) near30 (decreas\$5 decreas\$4 drop\$5 reduc\$5 fail\$5) near30 (gap)) transponder and ((electromagnetic electro-magnetic) near30 (decreas\$5 decreas\$4 drop\$5 reduc\$5 fail\$5) near30 (gap)) transponder and ((electromagnetic electro-magnetic) near30 (decreas\$5 decreas\$4 drop\$5 reduc\$5 fail\$5) near30 (between)) transponder and (induct\$7 near30 stray near30 (capacitance)) 1 delectromagnetic electro-magnetic) and (induct\$7 near30 stray near30 (capacitance)) 299 (electromagnetic electro-magnetic) and (induct\$7 near30 stray near30 (capacitance)) 299 (electromagnetic electro-magnetic) and (induct\$7 near30 stray near30 (capacitance)) 299 (455/\$.ccls. 340/\$.ccls. 370/\$.ccls.) and (electromagnetic electro-magnetic electro-magnetic) and (induct\$7 near30 stray near30 (capacitance))		•			
(decreas\$5 decreas\$4 drop\$5 reduc\$5 fail\$5) near30 (between)) 1 transponder and ((electromagnetic electro-magnetic) near30 (decreas\$5 decreas\$4 drop\$5 reduc\$5 fail\$5) near30 (gap)) transponder and ((electromagnetic electro-magnetic) near30 (decreas\$5 decreas\$4 drop\$5 reduc\$5 fail\$5) near30 (decreas\$5 decreas\$4 drop\$5 reduc\$5 fail\$5) near30 (decreas\$5 decreas\$4 drop\$5 reduc\$5 fail\$5) near30 (between)) 1 transponder and (induct\$7 near30 stray near30 (capacitance)) 1 transponder and (induct\$7 near30 stray near30 (capacitance)) 1 (electromagnetic electro-magnetic) and (induct\$7 near30 stray near30 stray near30 (capacitance)) 2 (electromagnetic electro-magnetic) and (induct\$7 near30 stray near30 (capacitance)) 2 (electromagnetic electro-magnetic) and (induct\$7 near30 stray near30 (capacitance)) 2 (electromagnetic electro-magnetic) and (electromagnetic electro-magnetic) and (induct\$7 near30 stray near30 (capacitance))	-	15		USPAT	2004/06/03 09:35
(between)) transponder and ((electromagnetic electro-magnetic) near30 (decreas\$5 decreas\$4 drop\$5 reduc\$5 fail\$5) near30 (gap)) transponder and ((electromagnetic electro-magnetic) near30 (decreas\$5 decreas\$4 drop\$5 reduc\$5 fail\$5) near30 (decreas\$5 decreas\$4 drop\$5 reduc\$5 fail\$5) near30 (between)) 1 transponder and (induct\$7 near30 stray near30 (capacitance)) 1 (electromagnetic electro-magnetic) and (induct\$7 near30 stray near30 stray near30 (capacitance)) 2004/06/03 09 DERWENT; IBM_TDB EPO; JPO; DERWENT; IBM_TDB EPO; JPO; DERWENT; IBM_TDB USPAT 2004/06/03 10: DERWENT; IBM_TDB USPAT 2004/06/					
(decreas\$5 decreas\$4 drop\$5 reduc\$5 fail\$5) near30 (gap)) transponder and ((electromagnetic electro-magnetic) near30 (decreas\$5 decreas\$4 drop\$5 reduc\$5 fail\$5) near30 (decreas\$5 decreas\$4 drop\$5 reduc\$5 fail\$5) near30 (decreas\$5 decreas\$4 drop\$5 reduc\$5 fail\$5) near30 DERWENT; IBM_TDB EPO; JPO; DERWENT; IBM_TDB EPO; JPO; DERWENT; IBM_TDB EPO; JPO; DERWENT; IBM_TDB EPO; JPO; DERWENT; IBM_TDB USPAT 2004/06/03 10: 0 delectromagnetic electro-magnetic) and (induct\$7 near30 stray near30 (capacitance)) 0 electromagnetic electro-magnetic) and (electromagnetic electromagnetic electromagnetic) and (induct\$7 near30 stray near30 (capacitance)) 0 electromagnetic) and (induct\$7 near30 stray near30 (capacitance)) 0 electro-magnetic) and (induct\$7 near30 stray near30 (capacitance))					
transponder and ((electromagnetic electro-magnetic) near30 (decreas\$5 decreas\$4 drop\$5 reduc\$5 fail\$5) near30 (DERWENT; IBM_TDB transponder and (induct\$7 near30 stray near30 (capacitance)) 1 (electromagnetic electro-magnetic) and (induct\$7 near30 stray near30 stray near30 (capacitance)) 1 (electromagnetic electro-magnetic) and (induct\$7 near30 stray near30 (capacitance)) 29 (electromagnetic electro-magnetic) and (induct\$7 near30 stray near30 (capacitance)) 29 (455/\$.ccls. 340/\$.ccls. 370/\$.ccls.) and (electromagnetic electro-magnetic) electro-magnetic) and (induct\$7 near30 stray near30 (capacitance)) 2004/06/03 10. 2004/06/03 10. 2004/06/03 10. 2004/06/03 10. 2004/06/03 10.	-	0	transponder and ((electromagnetic electro-magnetic) near30	USPAT	2004/06/03 09:20
(decreas\$5 decreas\$4 drop\$5 reduc\$5 fail\$5) near30 (between)) 1 transponder and (induct\$7 near30 stray near30 (capacitance)) 1 (electromagnetic electro-magnetic) and (induct\$7 near30 stray near30 stray near30 (capacitance)) 29 (electromagnetic electro-magnetic) and (induct\$7 near30 stray near30 (capacitance)) 29 (electromagnetic electro-magnetic) and (induct\$7 near30 stray near30 (capacitance)) 29 (455/\$.ccls. 340/\$.ccls. 370/\$.ccls.) and (electromagnetic electro-magnetic) electro-magnetic) and (induct\$7 near30 stray near30 (capacitance))			(decreas\$5 decreas\$4 drop\$5 reduc\$5 fail\$5) near30 (gap))	4	
(between)) transponder and (induct\$7 near30 stray near30 (capacitance)) 13 (electromagnetic electro-magnetic) and (induct\$7 near30 stray near30 (capacitance)) 13 (electromagnetic electro-magnetic) and (induct\$7 near30 stray near30 (capacitance)) 29 (electromagnetic electro-magnetic) and (induct\$7 near30 stray near30 (capacitance)) 29 (455/\$.ccls. 340/\$.ccls. 370/\$.ccls.) and (electromagnetic electro-magnetic) and (induct\$7 near30 stray near30 (capacitance)) 2004/06/03 10. 2004/06/03 10. 2004/06/03 10. 2004/06/03 10. 2004/06/03 10. 2004/06/03 10. 2004/06/03 10. 2004/06/03 10.	-	4			2004/06/03 09:55
transponder and (induct\$7 near30 stray near30 (capacitance)) 13 (electromagnetic electro-magnetic) and (induct\$7 near30 stray near30 (capacitance)) 13 (electromagnetic electro-magnetic) and (induct\$7 near30 stray near30 (capacitance)) 29 (electromagnetic electro-magnetic) and (induct\$7 near30 stray near30 (capacitance)) 29 (455/\$.ccls. 340/\$.ccls. 370/\$.ccls.) and (electromagnetic electro-magnetic) and (induct\$7 near30 stray near30 (capacitance)) 2004/06/03 10 2004/06/03 10 2004/06/03 10 2004/06/03 10 2004/06/03 10 2004/06/03 10			(decreas\$5 decreas\$4 drop\$5 reduc\$5 fail\$5) near30		
- 13 (electromagnetic electro-magnetic) and (induct\$7 near30 stray near30 (capacitance)) - 299 (electromagnetic electro-magnetic) and (induct\$7 near30 stray near30 (capacitance)) - 29 (455/\$.ccls. 340/\$.ccls. 370/\$.ccls.) and (electromagnetic electro-magnetic electro-magnetic) and (induct\$7 near30 (capacitance)) - 29 (455/\$.ccls. 340/\$.ccls. 370/\$.ccls.) and (electromagnetic electro-magnetic) and (induct\$7 near30 stray near30 (capacitance))					
- 13 (electromagnetic electro-magnetic) and (induct\$7 near30 stray near30 (capacitance)) - 299 (electromagnetic electro-magnetic) and (induct\$7 near30 stray near30 (capacitance)) - 29 (455/\$.ccls. 340/\$.ccls. 370/\$.ccls.) and (electromagnetic electro-magnetic electro-magnetic) and (induct\$7 near30 (capacitance)) - 29 (455/\$.ccls. 340/\$.ccls. 370/\$.ccls.) and (electromagnetic electro-magnetic) and (induct\$7 near30 stray near30 (capacitance))	-	1	transponder and (induct\$7 near30 stray near30 (capacitance))		2004/06/03 10:51
- 13 (electromagnetic electro-magnetic) and (induct\$7 near30 stray near30 (capacitance)) - 299 (electromagnetic electro-magnetic) and (induct\$7 near30 stray near30 (capacitance)) - 29 (455/\$.ccls. 340/\$.ccls. 370/\$.ccls.) and (electromagnetic electro-magnetic electro-magnetic) and (induct\$7 near30 stray near30 (capacitance)) USPAT 2004/06/03 10. 2004/06/03 10. 2004/06/03 10.					
near30 (capacitance)) DERWENT; IBM_TDB USPAT 299 (electromagnetic electro-magnetic) and (induct\$7 near30 stray near30 (capacitance)) 29 (455/\$.ccls. 340/\$.ccls. 370/\$.ccls.) and (electromagnetic electro-magnetic) and (induct\$7 near30 stray near30 (capacitance)) USPAT 2004/06/03 11:					
- 299 (electromagnetic electro-magnetic) and (induct\$7 near30 stray near30 (capacitance)) - 29 (455/\$.ccls. 340/\$.ccls. 370/\$.ccls.) and (electromagnetic electro-magnetic) and (induct\$7 near30 stray near30 (capacitance)) USPAT 2004/06/03 11:	-	13			2004/06/03 10:52
- 299 (electromagnetic electro-magnetic) and (induct\$7 near30 stray near30 (capacitance)) - 29 (455/\$.ccls. 340/\$.ccls. 370/\$.ccls.) and (electromagnetic electro-magnetic) and (induct\$7 near30 stray near30 (capacitance)) USPAT 2004/06/03 10: 2004/06/03			near30 (capacitance))		•
near30 (capacitance)) - 29 (455/\$.ccls. 340/\$.ccls. 370/\$.ccls.) and (electromagnetic electro-magnetic) and (induct\$7 near30 stray near30 (capacitance))		200	(1) - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 -		0004/00/00 40 50
- 29 (455/\$.ccls. 340/\$.ccls. 370/\$.ccls.) and (electromagnetic electro-magnetic) and (induct\$7 near30 stray near30 (capacitance))	-	299		USPAT	2004/06/03 10:53
electro-magnetic) and (induct\$7 near30 stray near30 (capacitance))		20		LICDAT	2004/06/02 44:44
(capacitance))	-	29		USPAI	2004/06/03 11:11
l = − − − − − − − − − − − − − − − − − −	_	22	(capacitance)) (455/\$.ccls. 340/\$.ccls. 370/\$.ccls.) and (elect\$5 adj field) and	USPAT	2004/06/03 11:10
(induct\$7 near30 stray near30 (capacitance))	-	22		JOPAI	2004/00/03 11.10
	_	58		USPAT	2004/06/03 11:17
(induct\$7 near30 stray near30 (capacitance))				33.7.1	230 1100/00 11.17